5.6.9 Typical Efficacies and Lifetimes of Lamps (1)

	Efficacy	Typical Rated	
Current Technology	(lumens/Watt)	Lifetime (hours)	CRI (2)
Incandescent	10 - 19	750 - 2,500	97
Halogen	14 - 20	2,000 - 3,500	99
Fluorescent - T5	25 - 55	6,000 - 7,500	52 - 75
Fluorescent - T8	35 - 87	7,500 - 20,000	52 - 90
Fluorescent - T12	35 - 92	7,500 - 20,000	50 - 92
Compact Fluorescent	40 - 70	10,000	82
Mercury Vapor	25 - 50	29,000	15 - 50
Metal Halide	50 - 115	30,00 - 20,000	65 - 70
High-Pressure Sodium	50 - 124	29,000	22
Low-Pressure Sodium	18 - 180	18,000	0
Solid State Lighting	(3)	(4)	70-80

Note(s): 1) Theoretical maximum luminous efficacy of white light is 220 lumens/Watt. 2) CRI = Color Rendition Index, which indicates a lamp's ability to show natural colors. 3) The DOE Solid State Lighting program has set an efficacy goal twice that of fluorescent lights (160 lumen per Watt). 4) Has not been determined.

Source(s): DOE, EERE, Building Technology Program/Navigant Consulting, U.S. Lighting Market Characterization, Volume I: National Lighting Inventory and Energy Consumption Estimate, Sept. 2002, Appendix A, p. 74; DOE/Navigant Consulting, Solid State Lighting Research and Development

Portfolio, Mar. 2006, p 55.